



STT60GKxx

Thyristor-Thyristor Modules



Type	V_{RSM} V_{DSM} V	V_{RRM} V_{DRM} V
STT60GK08	900	800
STT60GK12	1300	1200
STT60GK14	1500	1400
STT60GK16	1700	1600
STT60GK18	1900	1800

Dimensions in mm (1mm=0.0394")



Symbol	Test Conditions	Maximum Ratings	Unit
I_{TRMS}, I_{FRMS} I_{TAVM}, I_{FAVM}	$T_V = T_{VJM}$ $T_C = 83^\circ\text{C}; 180^\circ \text{ sine}$ $T_C = 85^\circ\text{C}; 180^\circ \text{ sine}$	100 64 60	A
I_{TSM}, I_{FSM}	$T_V = 45^\circ\text{C}$ $V_R = 0$ $t = 10\text{ms (50Hz), sine}$ $t = 8.3\text{ms (60Hz), sine}$ $T_V = T_{VJM}$ $V_R = 0$ $t = 10\text{ms (50Hz), sine}$ $t = 8.3\text{ms (60Hz), sine}$	1500 1600 1350 1450	A
i^2dt	$T_V = 45^\circ\text{C}$ $V_R = 0$ $T_V = T_{VJM}$ $V_R = 0$ $t = 10\text{ms (50Hz), sine}$ $t = 8.3\text{ms (60Hz), sine}$	11200 10750 9100 8830	A^2s
$(di/dt)_{cr}$	$T_V = T_{VJM}$ $f = 50\text{Hz}, t_p = 200\mu\text{s}$ $V_D = 2/3 V_{DRM}$ $I_G = 0.45\text{A}$ $di_G/dt = 0.45\text{A}/\mu\text{s}$ repetitive, $I_T = 150\text{A}$ non repetitive, $I_T = I_{TAVM}$	150 500	A/ μs
$(dv/dt)_{cr}$	$T_V = T_{VJM};$ $R_{GK} = \infty$; method 1 (linear voltage rise) $V_{DR} = 2/3 V_{DRM}$	1000	V/ μs
P_{GM}	$T_V = T_{VJM}$ $I_T = I_{TAVM}$ $t_p = 30\mu\text{s}$ $t_p = 300\mu\text{s}$	10 5	W
P_{GAV}		0.5	W
V_{RGM}		10	V
T_V T_{VJM} T_{stg}		-40...+125 125 -40...+125	$^\circ\text{C}$
V_{ISOL}	50/60Hz, RMS $I_{ISOL} \leq 1\text{mA}$ $t = 1\text{min}$ $t = 1\text{s}$	3000 3600	V~
M_d	Mounting torque (M5) Terminal connection torque (M5)	2.5-4.0/22-35 2.5-4.0/22-35	Nm/lb.in.
Weight	Typ.	81	g

Sirectifier®

STT60GKxx

Thyristor-Thyristor Modules

Symbol	Test Conditions	Characteristic Values	Unit
I_{RRM}, I_{DRM}	$T_{VJ}=T_{VJM}; V_R=V_{RRM}; V_D=V_{DRM}$	5	mA
V_T, V_F	$I_T, I_F=200A; T_{VJ}=25^{\circ}C$	1.57	V
V_{TO}	For power-loss calculations only ($T_{VJ}=125^{\circ}C$)	0.85	V
r_T		3.7	m Ω
V_{GT}	$V_D=6V; T_{VJ}=25^{\circ}C$ $T_{VJ}=-40^{\circ}C$	1.5 1.6	V
I_{GT}	$V_D=6V; T_{VJ}=25^{\circ}C$ $T_{VJ}=-40^{\circ}C$	100 200	mA
V_{GD}	$T_{VJ}=T_{VJM}; V_D=2/3V_{DRM}$	0.2	V
I_{GD}		10	mA
I_L	$T_{VJ}=25^{\circ}C; t_p=10\mu s; V_D=6V$ $I_G=0.45A; di_G/dt=0.45A/\mu s$	450	mA
I_H	$T_{VJ}=25^{\circ}C; V_D=6V; R_{GK}=\infty$	200	mA
t_{gd}	$T_{VJ}=25^{\circ}C; V_D=1/2V_{DRM}$ $I_G=0.45A; di_G/dt=0.45A/\mu s$	2	μs
t_q	$T_{VJ}=T_{VJM}; I_T=150A; t_p=200\mu s; -di/dt=10A/\mu s$ $V_R=100V; dv/dt=20V/\mu s; V_D=2/3V_{DRM}$ typ.	150	μs
Q_s	$T_{VJ}=T_{VJM}; I_T, I_F=50A; -di/dt=3A/\mu s$	100	μC
I_{RM}		24	A
R_{thJC}	per thyristor/diode; DC current per module	0.45 0.225	K/W
R_{thJK}	per thyristor/diode; DC current per module	0.65 0.325	K/W
d_s	Creeping distance on surface	12.7	mm
d_A	Strike distance through air	9.6	mm
a	Maximum allowable acceleration	50	m/s ²

FEATURES

- * International standard package
- * DCB base plate
- * Glass passivated chips
- * Isolation voltage 3600 V~
- * UL file NO.310749
- * RoHS compliant

APPLICATIONS

- * DC motor control
- * Softstart AC motor controller
- * Light, heat and temperature control

ADVANTAGES

- * Space and weight savings
- * Simple mounting with two screws
- * Improved temperature and power cycling
- * Reduced protection circuits

STT60GKxx

Thyristor-Thyristor Modules




Fig.1L Power dissipation per thyristor vs. on-state current




Fig.1R Power dissipation per thyristor vs. ambient temp




Fig.2L Power dissipation per module vs. rms current




Fig.2R Power dissipation per module vs. case temp




Fig.3L Power dissipation of two modules vs. direct current




Fig.3R Power dissipation of two modules vs. case temp

Sirectifier®

STT60GKxx

Thyristor-Thyristor Modules




Fig.4L Power dissipation of three modules vs. direct and rms current




Fig.4R Power dissipation of three modules vs. case temp




Fig.5 Recovered charge vs. current decrease




Fig.6 Transient thermal impedance vs. time




Fig.7 On-state characteristics




Fig.8 Surge overload current vs. time