

Power DomiLED

With its significant power in terms brightness, viewing angle and variety of application possibilities, Power DomiLED truly is a standout performer! Ideal for automotive interior lighting as well as home, office and industrial applications, it is also a proven performer in electronic signs and signals.



Features:

- > High brightness surface mount LED using thin film technology.
- > 120° viewing angle.
- > Small package outline (LxWxH) of 3.2 x 2.8 x 1.8mm.
- > Qualified according to JEDEC moisture sensitivity Level 2.
- > Compatible to IR reflow soldering.
- > Environmental friendly; RoHS compliance.
- > Compliance to automotive standard; AEC-Q101.



Applications:

> Automotive:

Interior applications, eg: switches, telematics, climate control system, dashboard, etc.

Exterior applications, eg: signal lighting, Center High Mounted Stop Light (CHMSL)

> Signage: full colour display video notice board, signage, special effect lighting.

> Industrial: white goods (eg: Oven, microwave, etc.), light bar, illuminated advertising.

> Lighting: architecture lighting, general lighting, garden light, channel light.



Optical Characteristics at Tj=25°C

Part Ordering Number	Color	Viewing Angle°	Luminous Flux <i>Appx. 1.2</i> @ IF = 50mA IV (lm)			Luminous Intensity <i>Appx. 1.1</i> @ IF = 50mA IV (mcd)
			Min.	Typ.	Max.	Typ.
DWS-HJS-F3H2-3	Super Red, 635nm	120	3.22	4.20	5.50	1400.00
DWS-HJS-GH3-2	Super Red, 630nm	120	3.68	4.90	6.30	1633.00
DWA-HJS-JK3-4	Amber, 624nm	120	6.30	8.20	10.70	2733.00
DWA-HJS-J3L2-2	Amber, 615nm	120	7.15	9.35	12.20	3116.00
DWY-HJS-J3L2-1	Yellow, 589nm	120	7.15	9.35	12.20	3116.00

Electrical Characteristics at Tj=25°C

Part Number	Vf @ If = 50mA <i>Appx. 3.1</i>			Vr @ Ir = 10uA <i>Appx. 6.1</i>
	Min. (V)	Typ. (V)	Max. (V)	Min. (V)
DWx-HJS	2.05	2.30	2.65	12

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	70	mA
Peak pulse current; (tp ≤ 10μs, Duty cycle = 0.1)	100	mA
Reverse voltage <i>Appx. 6.1</i>	12	V
ESD threshold (HBM)	2	KV
LED junction temperature	125	°C
Operating temperature	-40 ... +100	°C
Storage temperature	-40 ... +100	°C
Power dissipation (at room temperature)	200	mW
Thermal resistance		
- Real Thermal Resistance		
Junction / ambient, R _{th JA real}	300	K/W
Junction / solder point, R _{th JS real}	90	K/W
- Electrical Thermal Resistance		
Junction / ambient, R _{th JA el}	240	K/W
Junction / solder point, R _{th JS el}	65	K/W
(Mounting on FR4 PCB, pad size ≥ 16 mm ² per pad)		

Wavelength Grouping at Tj= 25°C

Color	Group	Wavelength distribution (nm) <i>Appx. 2.2</i>
DWS; Super Red	Full	627 - 637
	W	627 - 630
	X	630 - 634
	Y	634 - 637
DWA; Amber	Full	612 - 627
	W	612 - 616
	X	616 - 620
	Y	620 - 624
	Z	624 - 627
DWY; Yellow	Full	586 - 595
	X	586 - 589
	Y	589 - 592
	Z	592 - 595

Luminous Flux Group at Tj=25°C

Brightness Group	Luminous Flux (lm) <i>Appx. 1.2</i>
F3	3.22 ... 3.68
G2	3.68 ... 4.20
G3	4.20 ... 4.90
H2	4.90 ... 5.50
H3	5.50 ... 6.30
J2	6.30 ... 7.15
J3	7.15 ... 8.20
K2	8.20 ... 9.35
K3	9.35 ... 10.70
L2	10.70 ... 12.20


Vf Bining (Optional) at Tj= 25°C

Vf @ If = 50mA	Forward Voltage (V) <i>Appx. 3.1</i>
V44	2.05 ... 2.20
V45	2.20 ... 2.35
V46	2.35 ... 2.50
V47	2.50 ... 2.65

Please consult sales and marketing for special part number to incorporate Vf binning.


Relative Luminous Flux Vs Forward Current

$$\Phi_V / \Phi_V(50\text{mA}) = f(I_F); T_j = 25^\circ\text{C}$$




Forward Current Vs Forward Voltage

$$I_F = f(V_F); T_j = 25^\circ\text{C}$$




Maximum Current Vs Temperature

$$I_F = f(T)$$



Relative Spectral Emission

$$\Phi_{rel} = f(\lambda); T_j = 25^\circ\text{C}; I_F = 50\text{mA}$$




Allowable Forward Current Vs Duty Ratio

$$(T_j = 25^\circ\text{C}; t_p \leq 10\mu\text{s})$$




Radiation Pattern




Relative Forward Voltage Vs Junction Temperature

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 50\text{mA}$$




Relative Luminous Intensity Vs Junction Temperature

$$I_V/I_V(25^\circ\text{C}) = f(T_j); I_F = 50\text{mA}$$




Relative Wavelength Vs Junction Temperature

$$\Delta \lambda_{dom} = \lambda_{dom} - \lambda_{dom}(25^\circ\text{C}) = f(T_j); I_F = 50\text{mA}$$




Power DomiLED • AlInGaP : DWx-HJS Package Outlines



Material


Material	
Lead-frame	Cu Alloy With Ag Plating
Package	High Temperature Resistant Plastic, PPA
Encapsulant	Epoxy
Soldering Leads	Sn-Sn Plating

Recommended Solder Pad



Taping and orientation

- Reels come in quantity of 2000 units.
- Reel diameter is 180 mm.




200 mm min. for $\varnothing 180$ reel.


200 mm min. for $\varnothing 330$ reel.

480 mm min. for $\varnothing 180$ reel.


960 mm min. for $\varnothing 330$ reel.



Packaging Specification



Packaging Specification




Average 1pc Power DomiLED

1 completed bag (2000pcs)

Weight (gram)

0.034


240 ± 10



Dimensions (mm)

Packing Box


210 x 210 x 16



For Power DomiLED

Cardboard Box Size	Dimensions (mm)	Empty Box Weight (kg)	Reel / Box
Super Small	325 x 225 x 190	0.38	9 reels MAX
Small	325 x 225 x 280	0.54	15 reels MAX
Medium	570 x 440 x 230	1.46	60 reels MAX
Large	570 x 440 x 460	1.92	120 reels MAX

Recommended Pb-free Soldering Profile



Appendix

1) **Brightness:**

- 1.1 Luminous intensity is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.2 Luminous flux is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.3 Radiant intensity is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).
- 1.4 Radiant flux is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 8 \%$ and an expanded uncertainty of $\pm 11 \%$ (according to GUM with a coverage factor of $k=3$).

2) **Color:**

- 2.1 Chromaticity coordinate groups are measured at current pulse 25 ms(typ) with an internal reproducibility of ± 0.005 and an expanded uncertainty of ± 0.01 (accordingly to GUM with a coverage factor of $k=3$).
- 2.2 Dominant wavelength is measured at current pulse 25 ms(typ) with an internal reproducibility of $\pm 0.5\text{nm}$ and an expanded uncertainty of $\pm 1\text{nm}$ (accordingly to GUM with a coverage factor of $k=3$).

3) **Voltage:**

- 3.1 Forward Voltage, V_f is measured when a current pulse of 8 ms(typ) with an internal reproducibility of $\pm 0.05\text{V}$ and an expanded uncertainty of $\pm 0.1\text{V}$ (accordingly to GUM with a coverage factor of $k=3$).

4) **Typical Values:**

- 4.1 At special conditions of LED manufacturing processes, typical data or calculated correlations of technical parameters only reflect the statistical figures. But not necessarily correspond to the actual parameters of each single product, which could differ from the typical data or calculated correlations or the typical characteristic line. These typical data may change whenever technical improvements happen.

5) **Tolerance of Measure**

- 5.1 Unless otherwise noted in drawing, tolerances are specified with ± 0.1 and dimension are specified in mm.

6) **Reverse Voltage:**

- 6.1 Not designed for reverse operation. Continuous reverse voltage can cause migration and LED damage.

Revision History

Page	Subjects	Date of Modification
-	Initial Release	28 Jun 2018

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

About Us

DOMINANT Opto Technologies is a dynamic company that is amongst the world's leading automotive LED manufacturers. With an extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing and development capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies, a ISO/TS 16949 and ISO 14001 certified company, can be found under <http://www.dominant-semi.com>.

Please contact us for more information:

DOMINANT Opto Technologies Sdn. Bhd.
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia
Tel: (606) 283 3566 Fax: (606) 283 0566
E-mail: sales@dominant-semi.com