

## MM74HC245A Octal 3-STATE Transceiver

### General Description

The MM74HC245A 3-STATE bidirectional buffer utilizes advanced silicon-gate CMOS technology, and is intended for two-way asynchronous communication between data buses. It has high drive current outputs which enable high speed operation even when driving large bus capacitances. This circuit possesses the low power consumption and high noise immunity usually associated with CMOS circuitry, yet has speeds comparable to low power Schottky TTL circuits.

This device has an active LOW enable input  $\overline{G}$  and a direction control input, DIR. When DIR is HIGH, data flows from the A inputs to the B outputs. When DIR is LOW, data flows from the B inputs to the A outputs. The MM74HC245A transfers true data from one bus to the other.

This device can drive up to 15 LS-TTL Loads, and does not have Schmitt trigger inputs. All inputs are protected from damage due to static discharge by diodes to  $V_{CC}$  and ground.

### Features


- Typical propagation delay: 13 ns
- Wide power supply range: 2–6V
- Low quiescent current: 80  $\mu$ A maximum (74 HC)
- 3-STATE outputs for connection to bus oriented systems
- High output drive: 6 mA (minimum)
- Same as the 645

### Ordering Code:

| Order Number  | Package Number | Package Description                                                         |
|---------------|----------------|-----------------------------------------------------------------------------|
| MM74HC245AWM  | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| MM74HC245ASJ  | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| MM74HC245AMTC | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| MM74HC245AN   | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

### Connection Diagram




### Truth Table

| Control Inputs |     | Operation       |
|----------------|-----|-----------------|
| $\overline{G}$ | DIR |                 |
| L              | L   | B data to A bus |
| L              | H   | A data to B bus |
| H              | X   | Isolation       |

H = HIGH Level  
L = LOW Level  
X = Irrelevant

## Logic Diagram



**Absolute Maximum Ratings**(Note 1)

(Note 2)

|                                                           |                         |
|-----------------------------------------------------------|-------------------------|
| Supply Voltage ( $V_{CC}$ )                               | -0.5 to +7.0V           |
| DC Input Voltage DIR and $\overline{G}$ pins ( $V_{IN}$ ) | -1.5 to $V_{CC} + 1.5V$ |
| DC Input/Output Voltage ( $V_{IN}$ , $V_{OUT}$ )          | -0.5 to $V_{CC} + 0.5V$ |
| Clamp Diode Current ( $I_{CD}$ )                          | $\pm 20$ mA             |
| DC Output Current, per pin ( $I_{OUT}$ )                  | $\pm 35$ mA             |
| DC $V_{CC}$ or GND Current, per pin ( $I_{CC}$ )          | $\pm 70$ mA             |
| Storage Temperature Range ( $T_{STG}$ )                   | -65°C to +150°C         |
| Power Dissipation ( $P_D$ )                               |                         |
| (Note 3)                                                  | 600 mW                  |
| S.O. Package only                                         | 500 mW                  |
| Lead Temperature ( $T_L$ )                                |                         |
| (Soldering 10 seconds)                                    | 260°C                   |

**Recommended Operating Conditions**

|                                                            | Min | Max      | Units |
|------------------------------------------------------------|-----|----------|-------|
| Supply Voltage ( $V_{CC}$ )                                | 2   | 6        | V     |
| DC Input or Output Voltage<br>( $V_{IN}$ , $V_{OUT}$ )     | 0   | $V_{CC}$ | V     |
| Operating Temperature Range ( $T_A$ )                      | -40 | +85      | °C    |
| Input Rise/Fall Times<br>( $t_r$ , $t_f$ ) $V_{CC} = 2.0V$ |     | 1000     | ns    |
| $V_{CC} = 4.5V$                                            |     | 500      | ns    |
| $V_{CC} = 6.0V$                                            |     | 400      | ns    |

**Note 1:** Maximum Ratings are those values beyond which damage to the device may occur.**Note 2:** Unless otherwise specified all voltages are referenced to ground.**Note 3:** Power Dissipation temperature derating — plastic "N" package: - 12 mW/°C from 65°C to 85°C.**DC Electrical Characteristics** (Note 4)

| Symbol          | Parameter                                       | Conditions                                                                                                           | V <sub>CC</sub> | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = −40 to 85°C | T <sub>A</sub> = −55 to 125°C | Units |
|-----------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------|-------------------|------------------------------|-------------------------------|-------|
|                 |                                                 |                                                                                                                      |                 | Typ                   | Guaranteed Limits |                              |                               |       |
| V <sub>IH</sub> | Minimum HIGH Level Input Voltage                |                                                                                                                      | 2.0V            |                       | 1.5               | 1.5                          | 1.5                           | V     |
|                 |                                                 |                                                                                                                      | 4.5V            |                       | 3.15              | 3.15                         | 3.15                          | V     |
|                 |                                                 |                                                                                                                      | 6.0V            |                       | 4.2               | 4.2                          | 4.2                           | V     |
| V <sub>IL</sub> | Maximum LOW Level Input Voltage                 |                                                                                                                      | 2.0V            |                       | 0.5               | 0.5                          | 0.5                           | V     |
|                 |                                                 |                                                                                                                      | 4.5V            |                       | 1.35              | 1.35                         | 1.35                          | V     |
|                 |                                                 |                                                                                                                      | 6.0V            |                       | 1.8               | 1.8                          | 1.8                           | V     |
| V <sub>OH</sub> | Minimum HIGH Level Output Voltage               | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 20 μA                                  | 2.0V            | 2.0                   | 1.9               | 1.9                          | 1.9                           | V     |
|                 |                                                 |                                                                                                                      | 4.5V            | 4.5                   | 4.4               | 4.4                          | 4.4                           | V     |
|                 |                                                 |                                                                                                                      | 6.0V            | 6.0                   | 5.9               | 5.9                          | 5.9                           | V     |
|                 |                                                 | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 6.0 mA<br> I <sub>OUT</sub>   ≤ 7.8 mA | 4.5V            | 4.2                   | 3.98              | 3.84                         | 3.7                           | V     |
|                 |                                                 |                                                                                                                      | 6.0V            | 5.7                   | 5.48              | 5.34                         | 5.2                           | V     |
|                 |                                                 |                                                                                                                      |                 |                       |                   |                              |                               |       |
| V <sub>OL</sub> | Maximum LOW Level Output Voltage                | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 20 μA                                  | 2.0V            | 0                     | 0.1               | 0.1                          | 0.1                           | V     |
|                 |                                                 |                                                                                                                      | 4.5V            | 0                     | 0.1               | 0.1                          | 0.1                           | V     |
|                 |                                                 |                                                                                                                      | 6.0V            | 0                     | 0.1               | 0.1                          | 0.1                           | V     |
|                 |                                                 | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br> I <sub>OUT</sub>   ≤ 6.0 mA<br> I <sub>OUT</sub>   ≤ 7.8 mA | 4.5V            | 0.2                   | 0.26              | 0.33                         | 0.4                           | V     |
|                 |                                                 |                                                                                                                      | 6.0V            | 0.2                   | 0.26              | 0.33                         | 0.4                           | V     |
|                 |                                                 |                                                                                                                      |                 |                       |                   |                              |                               |       |
| I <sub>IN</sub> | Input Leakage Current ( $\overline{G}$ and DIR) | V <sub>IN</sub> = V <sub>CC</sub> to GND                                                                             | 6.0V            |                       | ±0.1              | ±1.0                         | ±1.0                          | μA    |
| I <sub>OZ</sub> | Maximum 3-STATE Output Leakage Current          | V <sub>OUT</sub> = V <sub>CC</sub> or GND<br>Enable $\overline{G}$ = V <sub>IH</sub>                                 | 6.0V            |                       | ±0.5              | ±5.0                         | ±10                           | μA    |
| I <sub>CC</sub> | Maximum Quiescent Supply Current                | V <sub>IN</sub> = V <sub>CC</sub> or GND<br>I <sub>OUT</sub> = 0 μA                                                  | 6.0V            |                       | 8.0               | 80                           | 160                           | μA    |

**Note 4:** For a power supply of  $5V \pm 10\%$  the worst case output voltages ( $V_{OH}$ , and  $V_{OL}$ ) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst case  $V_{IH}$  and  $V_{IL}$  occur at  $V_{CC} = 5.5V$  and 4.5V respectively. (The  $V_{IH}$  value at 5.5V is 3.85V.) The worst case leakage current ( $I_{IN}$ ,  $I_{CC}$ , and  $I_{OZ}$ ) occur for CMOS at the higher voltage and so the 6.0V values should be used.

## AC Electrical Characteristics

$V_{CC} = 5V$ ,  $T_A = 25^\circ C$ ,  $t_r = t_f = 6ns$

| Symbol                | Parameter                   | Conditions                         | Typ | Guaranteed Limit | Units |
|-----------------------|-----------------------------|------------------------------------|-----|------------------|-------|
| $t_{PHL}$ , $t_{PLH}$ | Maximum Propagation Delay   | $C_L = 45 pF$                      | 12  | 17               | ns    |
| $t_{PZH}$ , $t_{PZL}$ | Maximum Output Enable Time  | $R_L = 1 k\Omega$<br>$C_L = 45 pF$ | 24  | 35               | ns    |
| $t_{PHZ}$ , $t_{PLZ}$ | Maximum Output Disable Time | $R_L = 1 k\Omega$<br>$C_L = 5 pF$  | 18  | 25               | ns    |

## AC Electrical Characteristics

$V_{CC} = 2.0V$  to  $6.0V$ ,  $C_L = 50 pF$ ,  $t_r = t_f = 6ns$  (unless otherwise specified)


| Symbol                                 | Parameter                                | Conditions              | V <sub>CC</sub> | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = −40 to 85°C |     | T <sub>A</sub> = −55 to 125°C |  | Units |
|----------------------------------------|------------------------------------------|-------------------------|-----------------|-----------------------|-------------------|------------------------------|-----|-------------------------------|--|-------|
|                                        |                                          |                         |                 | Typ                   | Guaranteed Limits |                              |     |                               |  |       |
| t <sub>PHL</sub> ,<br>t <sub>PLH</sub> | Maximum Propagation Delay                | C <sub>L</sub> = 50 pF  | 2.0V            | 31                    | 90                | 113                          | 135 | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 150 pF | 2.0V            | 41                    | 96                | 116                          | 128 | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 50 pF  | 4.5V            | 13                    | 18                | 23                           | 27  | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 150 pF | 4.5V            | 17                    | 22                | 28                           | 33  | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 50 pF  | 6.0V            | 11                    | 15                | 19                           | 23  | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 150 pF | 6.0V            | 14                    | 19                | 23                           | 28  | ns                            |  |       |
| t <sub>PZH</sub> ,<br>t <sub>PZL</sub> | Maximum Output Enable Time               | R <sub>L</sub> = 1 kΩ   | 2.0V            | 71                    | 190               | 240                          | 285 | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 50 pF  |                 | 81                    | 240               | 300                          | 360 | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 150 pF | 2.0V            | 81                    | 240               | 300                          | 360 | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 50 pF  | 4.5V            | 26                    | 38                | 48                           | 57  | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 150 pF | 4.5V            | 31                    | 48                | 60                           | 72  | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 50 pF  | 6.0V            | 21                    | 32                | 41                           | 48  | ns                            |  |       |
| t <sub>PHZ</sub> ,<br>t <sub>PLZ</sub> | Maximum Output Disable Time              | C <sub>L</sub> = 150 pF | 6.0V            | 25                    | 41                | 51                           | 61  | ns                            |  |       |
|                                        |                                          | R <sub>L</sub> = 1 kΩ   | 2.0V            | 39                    | 135               | 169                          | 203 | ns                            |  |       |
|                                        |                                          | C <sub>L</sub> = 50 pF  | 4.5V            | 20                    | 27                | 34                           | 41  | ns                            |  |       |
|                                        |                                          |                         | 6.0V            | 18                    | 23                | 29                           | 34  | ns                            |  |       |
| t <sub>TLH</sub> , t <sub>THL</sub>    | Output Rise and Fall Time                | C <sub>L</sub> =50 pF   | 2.0V            | 20                    | 60                | 75                           | 90  | ns                            |  |       |
|                                        |                                          |                         | 4.5V            | 6                     | 12                | 15                           | 18  | ns                            |  |       |
|                                        |                                          |                         | 6.0V            | 5                     | 10                | 13                           | 15  | ns                            |  |       |
| C <sub>PD</sub>                        | Power Dissipation Capacitance (Note 5)   | $\overline{G} = V_{IL}$ |                 | 50                    |                   |                              |     | pF                            |  |       |
|                                        |                                          | $\overline{G} = V_{IH}$ |                 | 5                     |                   |                              |     | pF                            |  |       |
| C <sub>IN</sub>                        | Maximum Input Capacitance                |                         |                 | 5                     | 10                | 10                           | 10  | pF                            |  |       |
| C <sub>IN/OUT</sub>                    | Maximum Input/Output Capacitance, A or B |                         |                 | 15                    | 20                | 20                           | 20  | pF                            |  |       |

**Note 5:**  $C_{PD}$  determines the no load dynamic power consumption,  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ , and the no load dynamic current consumption,  $I_S = C_{PD} V_{CC} f + I_{CC}$ .

**Physical Dimensions** inches (millimeters) unless otherwise noted



**20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  
Package Number M20B**



DETAIL A

NOTES:

A. CONFORMS TO EIAJ EDR-7320 REGISTRATION,  
ESTABLISHED IN DECEMBER, 1998.



B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M20DRevB1

**20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M20D**


# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



DIMENSIONS ARE IN MILLIMETERS

## NOTES:

- CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.
- DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.




DETAIL A

MTC20REVD1

20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  
Package Number MTC20

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



N20A (REV G)

20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide  
Package Number N20A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Fairchild Semiconductor:

[MM74HC245AWMX](#) [MM74HC245AMTCX](#) [MM74HC245ASJX](#) [MM74HC245AMTC](#) [MM74HC245AWM](#)  
[MM74HC245ASJ](#)