


## ■Features

- 5mm Round Standard Directivity
- Superior Weather-resistance
- UV Resistant Epoxy
- Water Clear Type
- Ammo Pack : 2K/Box

## ■Applications

- Traffic signal, Portable light source
- Signage and channel letter
- Decorating and entertainment lighting
- Architectural lighting
- Outdoor/Indoor applications/Other Lighting

## ■Outline Dimension




## ■Absolute Maximum Rating

(Ta=25°C)

| Item                       | Symbol    | Value       | Unit |
|----------------------------|-----------|-------------|------|
| DC Forward Current         | $I_F$     | 50          | mA   |
| Pulse Forward Current*     | $I_{FP}$  | 120         | mA   |
| Reverse Voltage            | $V_R$     | 5           | V    |
| Power Dissipation          | $P_D$     | 120         | mW   |
| Operating Temperature      | $T_{opr}$ | -40~ +85    | °C   |
| Storage Temperature        | $T_{stg}$ | -40 ~ +100  | °C   |
| Lead Soldering Temperature | $T_{sol}$ | 260°C /5sec | -    |

\*Pulse width Max.10ms , Duty ratio max 1/10

## ■Directivity



## ■Electrical -Optical Characteristics

(Ta=25°C)

| Item                | Symbol          | Condition  | Min. | Typ. | Max. | Unit |
|---------------------|-----------------|------------|------|------|------|------|
| DC Forward Voltage  | $V_F$           | $I_F=20mA$ | 1.8  | 2.1  | 2.4  | V    |
| DC Reverse Current  | $I_R$           | $V_R=5V$   | -    | -    | 10   | μA   |
| Domi. Wavelength*   | $\lambda_D$     | $I_F=20mA$ | 585  | 590  | 595  | nm   |
| Luminous Intensity* | $I_v$           | $I_F=20mA$ | 5800 | 7000 | -    | mcd  |
| 50% Power Angle     | $2\theta_{1/2}$ | $I_F=20mA$ | -    | 30   | -    | deg  |

\*1 Tolerance of dominant wavelength is ±1nm

\*2 Tolerance of luminous intensity is ±15%

## ■Maximum Forward Current

