

A1,B1,A12,B12	Drain*2 地線*2		A1,B1,A12,B12
A4,B4,A9,B9	Red 紅		A4,B4,A9,B9
A5	Blue 藍		A5
A6	Green 綠	Twist Pair 對絞	A6
A7	White 白		A7
A2	Blue 藍	Red 紅 Twist Pair 對絞	B11
A3	White 白		B10
GND	Drain 地線		GND
B11	Blue 藍	Orange 橙 Twist Pair 對絞	A2
B10	White 白		A3
GND	Drain 地線		GND
B2	Blue 藍	Green 綠 Twist Pair 對絞	A11
B3	White 白		A10
GND	Drain 地線		GND
A11	Blue 藍	Blue 藍 Twist Pair 對絞	B2
A10	White 白		B3
GND	Drain 地線		GND
A8	Red 紅		B8
B8	Black 黑		A8
Shell	Braid 編織		Shell
Conn.1	Wire Color	Mylar Color	Conn.2

Note:
* QC Important Dimension to Check.
* Connentor: USB3.1 Type C
* Waterproof Rate: IP68(Mated)
  (Immersion for 24 hours at a depth of 1 meter)
* Housing: Thermoplastic, Black
* Gasket: Thermoplastic, Black
* Cable: UL 2725 OD5.0mm, Blck

UNIT:mm

TOLERANCE ±0.5 mm

TITLE: USB, C TYPE, 2.0, CABLE W/SR M, M, MOLDING, QUICK

SCALE: Free | SHEET: 1 OF 1

REV.: 01 | SIZE: A4 | QC :Inspection Item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO: OTO-UC-30MM-QD8B01	DRAWN BY	DATE
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.