

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	0917161514 Active RAST 2.5 Connector System 2.50mm Pitch Appli-Mate RAST 2.5 IDT Housing, Direct/Indirect, Female Polarizing Rib Between Circuits 1 & 2	e, 6 Circuits,
Documents: <u>3D Model</u> <u>Drawing (PDF)</u> Product Specification	Application Specification 990330008-00 Packaging Specification PK-90871-001 PS-99020-0040-001 (PDF)	-001 (PDF)
Agency Certification CSA UL	LR19980 E29179	Series image - Reference only EU ELV Not Relevant
General Product Family Series Comments	IDT and Solder Connectors 91716 ""This Molex product is manufactured fro that has the following ratings, tested by in agencies:: a) A Glow Wire Ignition Tempe (GWIT) of at least 775 deg C per IEC 606 b) A Glow Wire Flammability Index (GWF 850 deg C per IEC 60695-2-12.and hence with the requirements set out in the Intern Standard IEC 60335-1 5th edition - house similar electrical appliances - safety, secti Resistance to heat and fire. <p><p> The using this product must determine its suit use in their particular application through other acceptable means as described in e glow-wire flammability test standard IEC 6 and any applicable product end-use stand If it is determined during the customer's e of suitability, that higher performance is re please contact Molex for possible product ""This Molex product is manufactured fro that has the following ratings, tested by in agencies:: a) A Glow Wire Ignition Tempe of at least 775 deg C per IEC 60695-2-13 Wire Flammability Index (GWFI) above 88 per IEC 60695-2-12.and hence complies requirements set out in the International S 60335-1 5th edition - household and simil application through testing or other accep as described in end-product glow-wire fla standard IEC 60695-2-11 and any applica end-use standard(s). <p> Th it is determine the customer's evaluation of suitability, th performance is required, please contact M possible product options.""" Yes RAST 2.5 Connector System RAST 2.5</p></p></p>	 dependent erature Serch Parts in this Series 91716 Series Mates With Appli-Mate RAST 2.5 Header 90861, 90860 Mates Mith the Standard IEC ar electrical e to heat is product eir particular table product ed during at higher dependent erature (GWIT) A poli-Mate RAST 2.5 Header 90861, 90860

UPC Use With

	822348367931 RAST standard interface
	RAST standard Interface
Use With Physical Circuits (Loaded) Circuits (maximum) Color - Resin Durability (mating cycles max) Flammability Gender Glow-Wire Capable Lock to Mating Part Material - Metal Material - Plating Mating Material - Plating Termination Material - Plating Termination Material - Resin Net Weight Number of Rows Packaging Type Panel Mount Pitch - Mating Interface Pitch - Termination Interface Plating min - Mating Plating min - Termination Polarized to Mating Part Stackable Temperature Range - Operating Tarmination Interface; Stule	AST standard interface 4 4 Natural (White) 10 94V-0 Female No None Phosphor Bronze Tin Tin Nylon 1.399/g 1 Tray No 2.50mm 1.016µm 1.016µm Yes No -20° to +120°C
Termination Interface: Style Wire Size AWG	IDT or Pierce 22, 24
Wile Size AWG	22, 24
Electrical Current - Maximum per Contact Voltage - Maximum	2.0A, 4.0A 32V AC
Solder Process Data Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers Application Specification Packaging Specification Product Specification Sales Drawing	990330008-000 PK-90871-001-001 PS-99020-0040-001 917160001-000

822348367931

This document was generated on 05/22/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex: 91716-1514