

Data Sheet

-----Part No : SS10GSCDD -----

Features:

- 1.Low power consumption.
- 2.High efficiency.
- 3.Reliable and rugged.
- 4.Chip Material: InGaN
- 5.Lens Color: Diffused
6. Source Color: **Green**




ATTENTION

OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
SENSITIVE DEVICES


Outline Dimensions:

Pack Dimensions (mm)



UNIT:mm

Radiation Characteristics



Sansen Technology Co., Ltd

www.sansentech.com

info@sansentech.com

Absolute Maximum Ratings at Ta=25 :

Parameter	Maximum	Unit
Power Dissipation	100	mW
Peak Forward Current (1/10 Duty Cycle,0.1ms Pulse Width)	70	mA
Continuous Forward Current	30	mA
Reverse Voltage	5	V
Operating temperature range	-40 to + 80	
Storage Temperature Range	-40 to + 100	
Lead Soldering Temperature [1.6mm(0.63") from body]	260 for 3 Seconds	

Electrical/Optical Characteristics at Ta=25 :

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Luminous Intensity	I_v	$I_F=20\text{mA}$	1000		1500	mcd
Dominant Wavelength	λ_d	$I_F=20\text{mA}$	520	525	530	nm
Viewing Angle	2 1/2	$I_F=20\text{mA}$	40		60	deg
Forward Voltage	V_F	$I_F=20\text{mA}$	2.9	3.1	3.5	V
Reverse Current	I_R	$V_R=5\text{V}$			10	μA

www.sansentech.com

info@sansentech.com